

# Product datasheet

Specifications



## Easy9 surge arrester - 3P + N - 400 V - 20000 A

EZ9L33720

### Main

Range of product	Easy9
Product or component type	Surge arrester
Device short name	Easy9 SPD
Poles	3P + N
Remote signalling	Without
Surge arrester type	Electrical distribution network
Earthing system	TN-S TT
Disconnecter device type	Associated circuit breaker at 400 V

### Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV + GDT
Nominal discharge current	Common mode: 10 kA (N/PE) Common mode: 10 kA (L/N)
Maximum discharge current	Differential mode: 20 kA L/N Differential mode: 20 kA N/PE
[Uc] maximum continuous operating voltage	Differential mode: 275 V L/N Differential mode: 275 V N/PE
Maximum [Up] voltage protection level	Differential mode <1.3 kV type 2 L/N
Local signalling	Green and red flag
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	8
Height	90 mm
Width	72 mm
Depth	66.2 mm
Colour	Grey (RAL 7035)
Response time	<= 25 ns
Connections - terminals	Tunnel type terminal (downside) 5...35 mm <sup>2</sup> solid or flexible
Tightening torque	3.5 N.m

### Environment

<b>Standards</b>	IEC 61643-11
<b>Product certifications</b>	EAC GOST
<b>IP degree of protection</b>	IP20 on terminal:
<b>Relative humidity</b>	5...90 %
<b>Operating altitude</b>	2000 m
<b>Ambient air temperature for operation</b>	-5...60 °C
<b>Ambient air temperature for storage</b>	-5...70 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	7.500 cm
<b>Package 1 Width</b>	8.000 cm
<b>Package 1 Length</b>	10.300 cm
<b>Package 1 Weight</b>	423.000 g
<b>Unit Type of Package 2</b>	S03
<b>Number of Units in Package 2</b>	24
<b>Package 2 Height</b>	30.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	10.780 kg